

## MULTI-BIN RECYCLING COMPACTOR COMPARISON CHART

MODEL	CG10	600C/B	R44	R6	R6X2	4000CB	4000CC
Capacity	2 ft <sup>3</sup> 0.05 m <sup>3</sup>	6 ft <sup>3</sup> 0.17 m <sup>3</sup>	18 ft <sup>3</sup> 0.51 m <sup>3</sup>	33 ft <sup>3</sup> 0.94 m <sup>3</sup>	61 ft <sup>3</sup> 1.73 m <sup>3</sup>	Compactor: 40 ft <sup>3</sup> / 1.14m <sup>3</sup> Baler: 30 ft <sup>3</sup> / 0.85m <sup>3</sup>	80 ft <sup>3</sup> 2.27m <sup>3</sup>
Number of Bins	1	1	4	6	8	Compactor & Baler	2
Unit Height	51" 1296mm	82" 2083mm	84" 2134mm	95" 2413mm	126" 3201mm	107" 2718mm	107" 2718mm
Unit Width	96" 2439mm	26" 661mm	40" 1016mm	71" 1804mm	80" 2032mm	56" 1423mm	56" 1423mm
Unit Depth	19" 483mm	22" 559mm	40" 1016mm	64" 1626mm	87" 2210mm	86" 2185mm	86" 2185mm
Deck Space	13ft <sup>2</sup> 1.21m <sup>2</sup>	4 ft <sup>2</sup> 0.38m <sup>2</sup>	11 ft <sup>2</sup> 1.03m <sup>2</sup>	32 ft <sup>2</sup> 2.98m <sup>2</sup>	49 ft <sup>2</sup> 4.56m <sup>2</sup>	33 ft <sup>2</sup> 3.07m <sup>2</sup>	33 ft <sup>2</sup> 3.07m <sup>2</sup>
Unit Weight	900 lb 409 kg	1,200 lb 545 kg	1,500 lb 681 kg	3,500 lb 1588 kg	5,900 lb 2677 kg	5,000 lb 2268 kg	5,000 lb 2268 kg
Cycle Time (Seconds)	60	30	60	40	45	60	60
Compaction Force (Maximum)	59000 lb 30 t	14,700 lb 7.4 t	9,400 lb 4.7 t	29,000 lb 14.5 t	29,000 lbs/38,000lbs 14.5 t/ 19t	60,000 lb 30 t	60,000 lb 30t
Electric 240V,480V (Three Phase)	5HP/ 15.5, 7.8 Amps	2HP/ 14 Amps	5HP/ 15.5, 7.8 Amps	5HP/ 15.5, 7.8 Amps	5HP/ 15.5, 7.8 Amps	5HP/ 15.5, 7.8 Amps	5HP/ 15.5, 7.8 Amps
Air Requirements (Minimum)	100PSI 7bar		100PSI 7bar	100PSI 7bar			100PSI 7bar
Air Requirements (Minimum)	75CFM 2m <sup>3</sup> /min		75CFM 2m <sup>3</sup> /min	75CFM 2m <sup>3</sup> /min			75CFM 2m <sup>3</sup> /min
Hydraulic System (Maximum)	3000PSI 210 bar	650 PSI 45.5 bar	3000PSI 210 bar	3000PSI 210 bar	3000PSI 210 bar	3000PSI 210 bar	3000PSI 210 bar

NOTE \*\*All measurements are rounded up to the nearest whole unit or decimal.